



IPC

BY TENNANT COMPANY

VACUUM CLEANERS - HIGH REACH SOLUTION

INDUSTRIAL

POWER MAX

3500

W

WATER LIFT

3800

mmH₂O

Flowmix On

AIRFLOW

600

m³/h

Flowmix Off

TANK CAPACITY

78

l

EXCLUSIVE FEATURES

- ▶ POLYESTER CARTRIDGE WITH PROTECTION
- ▶ INNOVATIVE GASKET
- ▶ STRONG METAL HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ TILTING TROLLEY
- ▶ LARGE TANGENTIAL INLET WITH CYCLONIC EFFECT
- ▶ SOLID AND ERGONOMIC TROLLEY FOR ALL TERRAIN WITH BIG RUBBER WHEELS
- ▶ LOCKING FRONT WHEELS
- ▶ DRAIN HOSE FOR QUICK DISPOSAL



MOST FREQUENTLY USE

GUTTER CLEANING

INTERNAL HIGH-LEVEL DUSTING AND CLEANING

DRAIN CLEARANCE OR STANDING WATER REMOVAL

ROOF CLEANING

HIGH LEVEL PROPERTY INSPECTION

COMPATIBLE WITH:

- Elite poles (p.15)
- Super light poles (p.16)
- Telescopic (p.17)
- Inspection cameras (p.18)

SPECS



TIPPING AND REMOVABLE TANK



DRAIN HOSE AND SIEVE



FLOWMIX - TO INCREASE WATERLIFT PERFORMANCE BY 60%

TECHNICAL DATA

		INDUSTRIAL
Code		ASD014191
TECHNICAL DATA		
Usage		WET & DRY
Motor		3x single stage HV
Power	W	3300 - 3600 max
Voltage	V	220 - 240
Waterlift	mmH ₂ O	2380 (FM OFF) / 3800 (FM ON)
Airflow	m ³ /h	400 (FM OFF) / 220 (FM ON)
Tank capacity/Material	l	78/steel
Cable length	m	8,5
Sound pressure level (en 60704-1; en 60704-2-1; iec 60335-2-69)	dB(A)	74
Diameter of front inlet (tangential) / Material	mm	60 / metal
Diameter of accessories	mm	-
Dimension (LxWxH)	mm	550x600x980
Weight	Kg	39

STANDARD EQUIPMENT

CODE: FTDP00583
DRY FILTERING KIT



CODE: MPVR28723
FASTENING PLASTIC RING



CODE: MPVR41815
CUFF: INLET TO HOSE
Ø50 mm



CODE: LAFN11455
INTERNAL BASKET FOR
LEAVES

